CMS631-Q470E
CMS631-H420E

Desktop

10th Gen Intel® Core™
ATX

intel IoT Solutions Alliance



Top View (CMS631-Q470E)

KEY FEATURES

DDR4

Q470E: 2 DDR4 UDIMM up to 128GB
H420E: 2 DDR4 UDIMM up to 64GB

4K High Resolution

Supports 4K/ 2K resolution

Multiple Displays

Q470E: VGA + DP++ + HDMI
H420E: VGA + DP++, VGA + HDMI, DP++ + HDM

Multiple Expansion

1 PCIe x16, 1 PCIe x4, 5 PCI, 1 M.2 M key, 1 M.2 E key

Rich I/O

2 Intel GbE, 6 COM
Q470E: 13 USB
H420E: 10 USB

BLOCK DIAGRAM



MECHANICAL DRAWING



SPECIFICATION

Model Name		CMS631-Q470E	CMS631-H420E
SYSTEM	**Processor**	10th Generation Intel® LGA 1200 Socket Processors, TDP support up to 125W Intel® Core™ i9-10900E (10 Cores, 20M Cache, up to 4.7 GHz); 65W Intel® Core™ i9-10900TE (10 Cores, 20M Cache, up to 4.5 GHz); 35W Intel® Core™ i7-10700E (8 Cores, 16M Cache, up to 4.5 GHz); 65W Intel® Core™ i7-10700TE (8 Cores, 16M Cache, up to 4.4 GHz); 35W Intel® Core™ i5-10500E (6 Cores, 12M Cache, up to 4.2 GHz); 65W Intel® Core™ i5-10500TE (6 Cores, 12M Cache, up to 3.7 GHz); 35W Intel® Core™ i3-10100E (4 Cores, 8M Cache, up to 3.8 GHz); 65W Intel® Core™ i3-10100TE (4 Cores, 8M Cache, up to 3.6 GHz); 35W Intel® Pentium® G6400E (2 Cores, 4M Cache, 3.8 GHz); 58W Intel® Celeron® G5900E (2 Cores, 2M Cache, 3.2 GHz); 58W Intel® Celeron® G5900TE (2 Cores, 2M Cache, 3.0 GHz); 35W	
	Chipset	Intel® Q470E Chipset	Intel® H420E Chipset
	Memory	Four 288-pin Non-ECC UDIMM up to 128GB Dual Channel DDR4 2400/2666/2933MHz	Two 288-pin Non-ECC UDIMM up to 64GB Dual Channel DDR4 2400/2666/2933MHz
	BIOS	AMI	AMI
GRAPHICS	**Controller**	Intel® HD Gen 9 Graphics	Intel® HD Gen 9 Graphics
	Feature	OpenGL 4.5, DirectX 12, OpenCL 2.1 **HW Decode:** AVC/H.264, MPEG2, VC1/WMV9, JPEG/MJPEG, HEVC/H265, VP8, VP9 **HW Encode:** MPEG2, AVC/H264, JPEG, HEVC/H265, VP8, VP9	OpenGL 4.5, DirectX 12, OpenCL 2.1 **HW Decode:** AVC/H.264, MPEG2, VC1/WMV9, JPEG/MJPEG, HEVC/H265, VP8, VP9 **HW Encode:** MPEG2, AVC/H264, JPEG, HEVC/H265, VP8, VP9
	Display	1 x VGA 1 x DP++ 1 x HDMI 1.4b **VGA:** resolution up to 1920x1200 @ 60Hz **DP++:** resolution up to 4096x2160 @ 60Hz **HDMI:** resolution up to 4096x2160 @ 24Hz	1 x VGA 1 x DP++ 1 x HDMI 1.4b **VGA:** resolution up to 1920x1200 @ 60Hz **DP++:** resolution up to 4096x2160 @ 60Hz **HDMI:** resolution up to 4096x2160 @ 24Hz
	Multiple Displays	**Triple Display:** VGA + DP++ + HDMI	**Dual Display:** VGA + DP++ / VGA + HDMI / DP++ + HDMI
EXPANSION	**Interface**	1 x PCIe x16 (Gen 3) 1 x PCIe x4 (Gen 3) 5 x PCI	1 x PCIe x16 (Gen 3) 1 x PCIe x4 (Gen 3) 5 x PCI
	M.2	1 x M.2 2242/2260/2280 M key (PCIe Gen3 x4 NVMe/SATA/Intel® Optane Memory support) 1 x M.2 2242/2260/2280 M key (PCIe Gen3 x1/SATA as option, MOQ required) 1 x M.2 2230 E key (PCIe Gen3 x2/USB 2.0 as option, MOQ required)	1 x M.2 2242/2260/2280 M key (SATA as option, MOQ required)
AUDIO	**Audio Codec**	Realtek ALC888	Realtek ALC888
ETHERNET	**Controller**	1 x Intel® I210AT PCIe (10/100/1000Mbps) 1 x Intel® I219LM/I219V with iAMT12.0 (10/100/1000Mbps) (only Core i9/i7/i5 supports iAMT)	1 x Intel® I210AT PCIe (10/100/1000Mbps) 1 x Intel® I219LM/I219V (10/100/1000Mbps)
REAR I/O	**Ethernet**	2 x GbE (RJ-45)	2 x GbE (RJ-45)
	Serial	1 x RS-232/422/485 (RS-232 w/ power) (DB-9)	1 x RS-232/422/485 (RS-232 w/ power) (DB-9)
	USB	2 x USB 3.2 Gen2 2 x USB 3.2 Gen1 2 x USB 2.0	4 x USB 3.2 Gen1 2 x USB 2.0
	Display	1 x VGA 1 x DP++ 1 x HDMI	1 x VGA 1 x DP++ 1 x HDMI
	Audio	1 x Line-out 1 x Mic-in 1 x Line-in (opt., MOQ required)	1 x Line-out 1 x Mic-in 1 x Line-in (opt., MOQ required)
INTERNAL I/O	**Serial**	1 x RS-232/422/485 (RS-232 w/ power) (2.54mm pitch) 4 x RS-232 (2.54mm pitch)	1 x RS-232/422/485 (RS-232 w/ power) (2.54mm pitch) 4 x RS-232 (2.54mm pitch)
	USB	2 x USB 3.2 Gen 1 4 x USB 2.0 (2.54mm pitch, colay vertical Type A, opt.: MOQ required) 1 x USB 2.0 vertical Type A	2 x USB 3.2 Gen 1 2 x USB 2.0 (2.54mm pitch, colay vertical Type A, opt.: MOQ required)
	Audio	1 x Front Audio Header 1 x S/PDIF	1 x Front Audio Header 1 x S/PDIF
	SATA	6 x SATA 3.0 (up to 6Gb/s) one SATA port share with M.2 M-key RAID 0/1/5/10	4 x SATA 3.0 (up to 6Gb/s) one SATA port share with M.2 M-key
	PS/2	1 x PS/2 (mini-DIN-6)	1 x PS/2 (mini-DIN-6)
	LPC	1 x LPC Supports LPC EXT-RS232/RS485 module	1 x LPC Supports LPC EXT-RS232/RS485 module
	DIO	1 x 16-bit DIO	1 x 16-bit DIO

SPECIFICATION

Model Name		CMS631-Q470E	CMS631-H420E
INTERNAL I/O	**SMBus**	1 x SMBus	1 x SMBus
WATCHDOG TIMER	**Output & Interval**	System Reset, Programmable via Software from 1 to 255 Seconds	System Reset, Programmable via Software from 1 to 255 Seconds
SECURITY	**TPM**	Infineon TPM2.0 (opt., MOQ required)	Infineon TPM2.0 (opt., MOQ required)
Power	**Type**	ATX	ATX
	Connector	8-pin ATX 12V power 24-pin ATX power	8-pin ATX 12V power 24-pin ATX power
	Consumption	**Typical:** i9-10900K: 3.3V @ 0.13A (0.429W); 5V @ 0.7A (3.5W); 12V @ 0.44A (5.28W) **Max.:** i9-10900K: 3.3V @ 0.18A (0.594W); 5V @ 1.59A (7.95W); 12V @ 14.22A (170.64W)	**Typical:** i9-10900K: 3.3V @ 0.13A (0.429W); 5V @ 0.7A (3.5W); 12V @ 0.44A (5.28W) **Max.:** i9-10900K: 3.3V @ 0.18A (0.594W); 5V @ 1.59A (7.95W); 12V @ 14.22A (170.64W)
	RTC Battery	CR2032 Coin Cell	CR2032 Coin Cell
OS Support	**Microsoft**	Windows 10 IoT Enterprise 64-bit Windows 11 GAC	Windows 10 IoT Enterprise 64-bit Windows 11 GAC
	Linux	Linux Ubuntu 20.04	Linux Ubuntu 20.04
Environment	**Temperature**	**Operating:** -5 to 65°C **Storage:** -40 to 85°C	**Operating:** -5 to 65°C **Storage:** -40 to 85°C
	Humidity	**Operating:** 5 to 90% RH **Storage:** 5 to 90% RH	**Operating:** 5 to 90% RH **Storage:** 5 to 90% RH
	MTBF	504,168 hrs @ 25°C ; 278,849 hrs @ 45°C ; 172,277 hrs @ 60°C ; 146,454 hrs @ 65°C **Calculation Model:** Telcordia Issue 4 **Environment:** GB, GC - Ground Benign, Controlled	521,024 hrs @ 25°C ; 292,119 hrs @ 45°C ; 181,960 hrs @ 60°C ; 155,038 hrs @ 65°C **Calculation Model:** Telcordia Issue 4 **Environment:** GB, GC - Ground Benign, Controlled
Mechanism	**Dimensions**	ATX Form Factor 305mm (12") x 244mm (9.6")	ATX Form Factor 305mm (12") x 244mm (9.6")
	Height	**PCB:** 1.6mm **Top Side:** 37.7mm **Bottom Side:** 3mm	**PCB:** 1.6mm **Top Side:** 37.7mm **Bottom Side:** 3mm
Certifications	**Certifications**	CE, FCC Class B, RoHS, UKCA	CE, FCC Class B, RoHS, UKCA

ORDERING INFORMATION

Model Name	P/N	Memory	GbE	M.2	RS-232 /422/485	USB 3.2 Gen2	USB 3.2 Gen1	USB 2.0	SATA	TPM 2.0	Power	Temp.
CMS631-H420EC	770-CMS6313-000G	2 DDR4 UDIMM	2	0	2	0	6	4	4	0	24-pin ATX/ 8-pin ATX 12V	-5 to 65°C
CMS631-Q470ECRM	770-CMS6313-100G	4 DDR4 UDIMM		1		2	4	7	6	0		
CMS631-H420EC	770-CMS6313-200G	2 DDR4 UDIMM		0		0	6	4	4	1		
CMS631-Q470ECRM	770-CMS6313-300G	4 DDR4 UDIMM		1		2	4	7	6	1		
CMS631-H420EC	770-CMS6313-400G	2 DDR4 UDIMM		1		0	6	4	3	0		

PACKING LIST

• 1 CMS631 motherboard	
• 1 COM port cables (Length: 300mm, 2 x COM ports)	A81-015026-023G
• 1 Serial ATA data cable (Length: 500mm)	332-553001-005G
• 1 I/O shield	A49-CMS631-000G

OPTIONAL ITEMS

• USB 2.0 port cable (Length: 350/398mm)	A81-001066-016G
• USB 3.1 Gen1 port cable (Length: 320mm)	A81-001196-023G
• COM port cable (Length: 300mm, 2 x COM ports)	A81-015026-023G
• Serial ATA data cable (Length: 500mm, W/LOCK)	332-553001-005G
• Serial ATA data cable (Length: 500mm, W/LOCK, 90D)	A81-002128-017G
• Thermal solution (For 35W, Height: 37.3mm)	A71-101107-000G
• Thermal solution (For 65W, Height: 74.47mm)	A71-101158-000G
• Thermal solution (For 95W, Height: 76.6mm)	A71-101143-000G
• DP to HDMI Dongle	612-D2H13M-000G
• EXT-RS232 (4 ports RS-232 LPC module)	770-EXTRS1-000G
• EXT-RS485 (4 ports RS-485 LPC module)	770-EXTRS1-100G
• M.2-COM4 (M.2 serial port module)	770-M2COM1-000G
• M.2-2LAN (M.2 LAN port module)	770-M22LN2-000G
• M.2-2PSE (M.2 PSE module)	770-M22PS2-000G

DFI reserves the right to change the specifications at any time prior to the product's release. Changes thereafter will be based on the product's revision. Please contact your sales representative for the exact revision offered in your area. All product names mentioned are trademarks of their respective companies. © September 8, 2026 DFI Inc.