EHL051

Atom

Intel® Atom® Processor
2.5" Pico-ITX

IoT Solutions Alliance





Bottom View



Top View

KEY FEATURES

DDR4

1 DDR4 3200MHz SODIMM

4K High Resolution

Supports 4K/2K resolution

Dual Display

HDMI + LVDS

Multiple Expansion

1 M.2 E Key,
1 M.2 B Key,
1 SATA

Rich I/O

2 Intel GbE, 2 COM,
2 USB 3.2 Gen2,
2 USB 2.0

BLOCK DIAGRAM



MECHANICAL DRAWING



SPECIFICATION

System	**Processor**	Intel® Atom Processor, Elkhart Lake **Industrial** Intel® Atom x6425RE, 4C, 1.9GHz, 12W Intel® Atom x6416RE, 4C, 1.7GHz, 9W (Performance Update) Intel® Atom x6214RE, 2C, 1.4GHz, 6W (Performance Update) **Embedded** Intel® Atom x6425E, 4C, 2.0GHz(3.0GHz), 12W Intel® Atom x6413E, 4C, 1.5GHz(3.0GHz), 9W Intel® Atom x6211E, 2C, 1.3GHz(3.0GHz), 6W **PC Client** Intel® Pentium J6412, 4C, 2.0GHz(2.6GHz),10W Intel® Celeron N6210, 2C 1.2GHz(2.6GHz), 6.5W	
	Memory	Single DDR4-3200 SODIMM Up to 32GB (in-band ECC support in embedded/industrial SKU)	
	BIOS	AMI SPI 256Mbit	
Graphics	**Controller**	Intel® HD Graphics	
	Feature	OpenGL 5.0, DirectX 12, OpenCL 2.1	
		HW Decode: AVC/H.264, MPEG2, VC1, WMV9, JPEG/MJPEG, HEVC/H.265, VP8, VP9, MVC HW Encode: AVC/H.264, JPEG/MJPEG, HEVC/H.265, VP8, VP9, MVC	
	Display	1 x HDMI 1 x LVDS	HDMI: resolution up to 4096×2160 @24Hz LVDS: dual channel 18/24-bit, resolution up to 1920x1200 @60Hz
	Dual Displays	HDMI + LVDS	
Expension	**Interface**	1 x M.2 2230 E Key (PCIe/USB2.0) (for Wi-Fi/BT) 1 x M.2 3042/2242 B Key (PCIe*/USB3.0/SATA), optional with 1 x SIM slot. (for 4G/5G) *PCIe share with SATA LED (BOM Optional)	
AUDIO	**Audio Codec**	Realtek ALC888S-VD2-GR	
Ethernet	**Controller**	2 x Intel® I226-V/IT (10/100/1000Mbps)	
Rear I/O	**Ethernet**	2 x GbE (RJ-45)	
	USB	2 x USB 3.2 Gen2	
	Display	1 x HDMI	
Internal I/O	**Serial**	2 x RS-232/422/485 (1.27mm pitch)	
	USB	2 x USB 2.0 (1.27mm pitch)	
	Display	1 x LVDS LCD Panel Connector 1 x LCD/Backlight Power (5V/12V)	
	Audio	1 x Audio (Line-out/Mic-in)	
	SATA	1 x SATA 3.0 (up to 6Gb/s) 1 x 5V SATA Power (support SATA LED by BOM option)	
	DIO	1 x 8-bit DIO	
	Front Panel	1 x front panel (power button/reset button, power LED, HDD act LED)	
	SMBus	1 x SMBus/I2C (Opt.) ***Enable smart battery interface upon request.**	
Watchdog Timer	**Output & Interval**	System Reset, Programmable via Software from 1 to 255 Seconds	
Security	**TPM**	dTPM2.0	
Power	**Type**	Single 12V +/-10% DC	
	Connector	2-pin Terminal Block 2-pin Vertical Type Connector (Opt.)	
	Consumption	Typical: J6426:12V @ 1.1A (13.2Watt) Max.: J6426:12V @ 1.6A (19.2Watt)	
	RTC Battery	CR2032 Coin Cell	
OS Support	**OS Support (UEFI Only)**	Windows 10 IoT Enterprise (64-bit)	Windows 11 GAC
		Linux	
Environment	**Temperature**	Operating: -5 to 65°C, -40 to 85 °C	Storage: -40 to 85°C
	Humidity	Operating: 5 to 90% RH	Storage: 5 to 90% RH
	MTBF	x6425RE: 563,338 hrs @ 25°C; 391,802 hrs @ 45°C ; 278,646 hrs @ 60°C; 146,635 hrs @ 85°C Calculation model: Telcordia Issue 4 Environment: GB, GC – Ground Benign, Controlled	
Mechanism	**Dimensions**	2.5" Pico-ITX Form Factor	100mm (3.94") x 72mm (2.83")
	Height	PCB: 1.6 mm	
		Top Side: 15 mm	
		Bottom Side: 8 mm	
Standards and Certifications	**Certifications**	CE, FCC, RoHS, UKCA, KC	

ORDERING INFORMATION

Model Name	P/N	Processor	Memory	Display	GbE	RS-232/ 422/485	USB 3.2 Gen2	USB 2.0	Power	Thermal	Temp.
EHL051-TCD-6425RE	770-EHL0511-000G	x6425RE	1 DDR4 SO-DIMM	HDMI + LVDS	2	2	2	2	12VDC	Fanless	-40 to 85°C
EHL051-TCD-6416RE	770-EHL0511-100G	x6416RE									-40 to 85°C
EHL051-TCD-6214RE	770-EHL0511-200G	x6214RE									-40 to 85°C
EHL051-TCD-6425E	770-EHL0511-300G	x6425E									-40 to 85°C
EHL051-TCD-6413E	770-EHL0511-400G	x6413E									-40 to 85°C
EHL051-TCD-6211E	770-EHL0511-500G	x6211E									-40 to 85°C
EHL051-BCD-J6412	770-EHL0511-600G	J6412									-5 to 65°C
EHL051-BCD-N6210	770-EHL0511-700G	N6210									-5 to 65°C

PACKING LIST

• 1 EHL051 board	
• 1 Serial ATA data cable (Length: 152mm)	A81-002000-000G
• 1 Y cable for SATA and inverter power (Length: 155mm)	A81-020016-018G
• 1 Heat spreader (Height: 11mm) for x6000 series	A71-808359-000G
for N/J series	A71-808359-010G

OPTIONAL ITEMS

• USB port cable (Length: 200mm)	A81-001084-016G
• 1 COM port cable (Length: 300mm)	A81-015050-016G
• Power adapter (60W, 12V, DC Jack)	671-106012-000G
• 2 pole terminal to DC Jack cable	A81-004013-000G
• 1 Audio cable (Length: 160mm)	A81-022037-016G
• 1 Heat sink	
for x6000 series -40~85°C (Height: 22.6mm)	A71-008182-020G
for N/J series -6~65°C (Height: 18.9mm)	A71-008182-010G

DFI reserves the right to change the specifications at any time prior to the product's release. Changes thereafter will be based on the product's revision. Please contact your sales representative for the exact revision offered in your area. All product names mentioned are trademarks of their respective companies. © June 22, 2026 DFI Inc.