ASRock Industrial

IMB-X1317

Micro-ATX Motherboard

KEY FEATURES

- Intel® Core™ Ultra Series 2 processors (Arrow Lake-S) with W880 chipset
- 4 x 288-pin ECC/non-ECC CU-DIMM DDR5 6400 MHz, U-DIMM DDR5 5600 MHz, up to 256GB (64GB per DIMM)
- 1 x PCIe x16 (Gen5), 1 x PCIe x8 (Gen5), 2 x PCIe x4 (Gen4), 2 x USB4/Thunderbolt™4, 10 x USB 3.2 Gen2, 1 x USB 2.0, 1 x M.2 Key E, 2 x M.2 Key M, 6 x COM, 8 x SATA3
- 3 x Intel 1 Gigabit LAN, 1 x Intel 2.5 Gigabit LAN
- Supports Quad display, 1 x HDMI 2.1, 2 x DP 2.1 (2 from Type-C), 1 x DP 1.4a, 1 x LVDS or eDP
- TPM 2.0 onboard IC
- Supports Intel® vPro, VMD RAID 0/1/5/10
- ATX Power (24+8+8-pin)

SPECIFICATIONS

Form Factor

Dimensions	Micro-ATX (9.6-in x 9.6-in x 1.81-in, 24.4 cm x 24.4 cm x 4.61 cm)

Processor System

CPU	Intel® Core™ Ultra Series 2 processors (Arrow Lake-S), up to 125W *Supports with a maximum power limit up to 252W
Chipset	W880
Socket	LGA1851
BIOS	AMI SPI 256 Mbit

Memory

Technology	Dual Channel ECC/non-ECC DDR5 6400/5600 MHz
Capacity	256GB (64GB per DIMM)
Socket	4 x 288-pin Long-DIMM

Graphics

Controller	Intel® Xe LPG Graphics
HDMI	HDMI 2.1 Max resolution up to 7680x4320@60Hz
DisplayPort	DisplayPort 2.1/1.4a, DP++ Max resolution up to 4096x2160@60Hz
LVDS	Dual channel 24 bit up to 1920x1200@60Hz (Connector shared with eDP)
eDP	Max resolution up to 1920x1200@60Hz (Connector shared with LVDS)
MultiDisplay	Quad display (Included 2 output from Type-C)

Expansion Slot

PCIe	2 x PCIe Gen5 Slots (PCIE1/PCIE4:single at x16 (PCIE1); dual at x8 (PCIE1)/x8 (PCIE4)) (PCIE1: Support Riser card x8/x8) 2 x PCIe x4 (Gen4)
M.2	1 x M.2 (Key E, 2230) with PCIe Gen4 x1, USB 2.0 and CNVi for Wireless

Audio

Interface	Realtek ALC897 HD, High Definition Audio. Line-In, Line-Out, Mic-In

Watchdog Timer

Output	From Super I/O to drag RESETCON#
Interval	256 Segments, 0, 1, 2, ...255sec

Ethernet

Controller/ Speed	LAN1: Intel® I210AT with 10/100/1000 Mbps LAN2: Intel® I210AT with 10/100/1000 Mbps LAN3: Intel® I219LM with 10/100/1000 Mbps, supports vPro LAN4: Intel® I226V with 10/100/1000/2500 Mbps
Connector	4 x RJ-45

Rear I/O

HDMI	1 x HDMI 2.1
DisplayPort	1 x DP 1.4a++
Ethernet	3 x 1 Gigabit LAN 1 x 2.5 Gigabit LAN
USB	7 x USB 3.2 Gen2 1 x USB4/Thunderbolt™4 (5V/3A, supports DP 2.1 display output) * For Thunderbolt support, please refer to support list.
Audio	3 (Mic-in, Line-in, Line-out)
COM	COM1 (RS-232/422/485)

Internal Connector

USB	1 x USB 2.0 (1 x 2.00 pitch header) 2 x USB 3.2 Gen2 (1 x USB 3.2 header) 1 x USB 3.2 Gen2 vertical Con 1 x USB4/Thunderbolt™4 vertical con. (5V/3A, supports DP 2.1 display output) * For Thunderbolt support, please refer to support list.
COM	COM2 (RS-232/422/485) COM3 (RS-232/TTL 5V/ccTalk) (Switch by Jumper setting) COM4, COM5, COM6 (RS-232)
Parallel	1 (shared with GPIO)
GPIO	8 x GPI, 8 x GPO (shared with LPT header)
LVDS	1 (Connector with LVDS/eDP signal, switch by BIOS)
Speaker Header	1
Thunderbolt header	1

Storage

M.2	1 x M.2 (Key M, 2242/2280) with PCIe Gen5 x4 for SSD 1 x M.2 (Key M, 2242/2280) with PCIe Gen4 x4 for SSD
SATA	8 x SATA3 (6Gb/s)
RAID	Intel® VMD RAID 0/1/5/10 **supported by identical interface (PCIE or SATA) PCIE interface: 2 x M.2 Key M SATA interface: SATA port

Security

TPM	TPM 2.0 onboard IC

Power Requirements

Input PWR	ATX PWR (24+8+8-pin)
Power On	AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready

Environment

Operating Temp	-20°C ~ 70°C
Storage Temp	-40°C ~ 85°C
Operating Humidity	5% ~ 90%
Storage Humidity	5% ~ 90%

The specification is subject to change without notice. The brand and product names are trademarks of their respective companies. Any configuration other than original product specification is not guaranteed.

BLOCK DIAGRAM



The specification is subject to change without notice. The brand and product names are trademarks of their respective companies. Any configuration other than original product specification is not guaranteed.

ORDERING INFORMATION

Ordering Information

Model	IMB-1317	IMB-X1317	IMB-X1317-10G
CPU/Chipset	Q870	W880	W880
HDMI	1	1	1
DP	1	1	1
LVDS/eDP	1/ (1)	1/ (1)	1/ (1)
1 Gbe LAN	1	3	3
2.5 Gbe LAN	1	1	1
10 Gbe LAN	0	0	1
COM	6	6	6
USB4/Thunderbolt™ 4 or USB Type-C	2	2	2
USB 3.2	10	10	10
USB 2.0	1	1	1
SATA III	8	8	8
M.2 E-Key	1	1	1
M.2 M-Key	2	2	2
TPM	1	1	1

Packing List (Gift)

Description	Quantity
SATA Data Cable	2
I/O Shield	1
SCREW M3*2.5	3

Packing List (Bulk)

Description	Quantity
I/O Shield	1
SCREW M3*2.5	3

Optional Accessories

P/N	Description
13G03P003000AI	DIMM BRACKET

I/O View

IMB-1317

IMB-X1317

IMB-X1317-10G

The specification is subject to change without notice. The brand and product names are trademarks of their respective companies. Any configuration other than original product specification is not guaranteed.