## ViviSign

#### SD265M 26.5" SQUARE LCD DISPLAY





#### **FULL HD DEFINITION**

FULL HD resolution 1920 x 1920 ensures vivid, high-impact images and videos in Museum, Exhibition halls, Shopping malls and Supermarkets.



#### **HIGHLY DURABLE SCREENS**

Designed for continuous use in public spaces, these displays utilise commercial grade LCD panels, LED backlights and internal components. This means they can run 24/7 for over 50,000 hours.



#### **ULTRA NARROW BEZEL**

These displays feature a slim border for applications where this is important, such as placing multiple screens side-by-side.



#### **IPS LCD PANEL**

IPS technology solution will get you ready for true-to-life colors, deep black levels and rich colors for amazing contrast and color.



#### **ANTI-GLARE LCD PANEL**

With an non-glare (25% haze) panel, you can rest assured that your content will not be obstructed by lighting conditions outside of your control.



#### **NATIVE SQUARE LCD**

Non-resizing/cutting LCD Panel, so no Broken glass, fragile sealing, microcracks, light leakage.



#### **OPT.1: LCD MONITOR**

Users can choose the stretched display as LCD Monitor with HDMI IN only, which allows to connect to any external media player or mini PC if required.



#### **OPT.2: ANDROID PLAYER**

Users can choose to integrated with Android player to update content via USB or CMS. You can also install any 3rd party CMS Software if required.

### SPECIFICATIONS

# UDE GIN

#### **Panel**

**Diagonal Size** 

26.5"

Resolution

1920 x 1920

**Brightness (Typ.)** 

300 nit

**Contrast Ratio** 

1000:1

Viewing Angle

178 / 178 (H/V)

Colors

16.7M. 99% sRGB

**Surface Treat.** 

Haze 25%

AA Area (mm)

475 776 × 475 776

**Power** 

**Type** External **Power Supply** 

AC 100 - 240V, 50/60Hz - DC 12V

**Power Consumption** 

60W

**Mechanical** 

Outline Size (mm)

501.2 x 503.2 x 33.6

Weight

10 kg

**Bracket** 

Optional

**Operation** 

**Operation Temp.** 

0 - 40°C

**Humidity** 

10% - 80%

**OPT.1: LCD Monitor with HDMI IN Only** 

**USB** 

USB x 1

**HDMI IN** 

HDMI IN x 1

**OPT.2: Android PC** 

CPU

**USB** 

USB 2.0 x 2

Quad-core Cortex A17

GPU

Mali-T764

**RAM** 

2GB

Optional

**Internal Memory** 

8GB

OS

Network **Bluetooth** 

LAN, Wi-Fi

Android OS 7.1

Web: www.vivisign.com

Email: info@vivisign.com