



Unlike other stretched signage that uses cut panels, Vivisign's stretched signage uses native stretched displays that feature a photo mask manufacturing process which ensures high quality and outstanding industrial-grade performance.



ULTRA HD DEFINITION

ULTRA HD resolution 3840 x 720 ensures vivid, high-impact images and videos at the point of sale.



EXCEPTIONAL BRIGHTNESS

Elevated brightness 700nits provides extraordinary colour expression and greater visibility. Ideal for brightly-lit retail spaces.



AUO TARTAN TECHNOLOGY

AUO's ultra-wide stretched displays, utilize AUO's unique Tartan display technology. These units offer a space saving, energy-efficient and reliable display solution.



HIGHLY DURABLE SCREENS

Designed for continuous use in public spaces, these displays utilize commercial grade LCD panels, LED backlights and internal components. The display can run 24/7 for over 50,000 hours.



ENHANCED COLOR GAMUT

92% NTSC Color Gamut delivers accurate and smooth color in brilliant 4K compared with traditional 72% NTSC in the market.



NATIVE STRETCHED LCD

Non-resizing/cutting LCD Panel, so no broken glass, fragile sealing, micro-cracks, light leakage.



OPT.1: LCD MONITOR

Users can choose the stretched display as LCD Monitor with HDMI IN only, which allows to connect to any external media player or mini PC if required.



OPT.2: ANDROID PLAYER

Users can choose to integrate with an Android player to update content via USB or CMS. You can also install any 3rd party CMS Software if required.

SPECIFICATIONS

Panel

Diagonal Size 43.1"	Resolution 3840 x 720	Brightness (Typ.) 700 nit	Contrast Ratio 4000:1
Viewing Angle 178 / 178 (H/V)	Colors 1.07B, 90% NTSC	Surface Treat. 28% Haze, AG	AA Area (mm) 1073.78 x 201.33

Power

Type Internal	Power Supply AC 100 - 240V, 50/60Hz	Power Consumption 100W
-------------------------	---	----------------------------------

Mechanical

Outline Size (mm) 1107.4 x 235.13 x 52	Weight 12 kg	Bracket x1
--	------------------------	----------------------

Operation

Operation Temp. 0 - 40 °C	Humidity 10% - 80%
-------------------------------------	------------------------------

OPT.1: LCD Monitor with HDMI IN Only

USB USB x 1	HDMI IN HDMI IN x 2
-----------------------	-------------------------------

OPT.2: Android PC

CPU Quad-core Cortex A53	GPU Mali-400 MP2	RAM 2GB	Internal Memory 8GB
USB USB 2.0 x 2	Network LAN, Wi-Fi	Bluetooth BT4.0	OS Android OS 7.1

Upgradable

Higher Performance Android Mainboard is Available if required