F65EAC-IAD32

Waterproof Full IP65 EAC Box PC with M12 Connector, Intel® Core™ i5-1235U

KEY FEATURES

- Intel® 12th Generation Core™ i5-1235U Processor
- 1 x SO-DIMM, DDR5 4800 MHz (Max. 32GB)
- 1 x M.2 Key M Slot for M.2 2280 NVME SSD
- Full IP65 Rugged Embedded PC
- Full Aluminum Alloy Enclosure with fin
- Fnless design with M12 waterproof connector
- Wide Range 9 to 36V DC Input with isolation

INTRODUCTION

Winmate Waterproof Full IP65 EAC Box PC Series is a rugged, fanless solution designed to operate reliably in extreme industrial environments. Featuring full IP65 protection, aluminum alloy housing, and M12 waterproof connectors, it resists dust, water, vibrations, and electromagnetic interference. Powered by 11th and 12th Gen Intel® Core™ processors, with support for DDR5 RAM and M.2 NVMe SSDs, these compact Box PCs deliver high performance and flexibility. Ideal for manufacturing, transportation, and harsh outdoor settings, they ensure durability and seamless connectivity in demanding conditions.

SPECIFICATIONS

System Specification

WLAN	Support (Optional)	**BT**	Support (Optional)
Processor	Intel® Core™ i5-1235U 3.3GHz(up to 4.40 GHz)	**Memory**	8GB(Default) (Default) 16GB (Optional) 32GB (Optional)
Storage	128GB SSD(Default) (Default) 256GB SSD (Optional) 512GB SSD (Optional) 1TB (Optional) 2TB (Optional) 4TB (Optional)	**Ethernet controller**	2 x Intel® Ethernet Controller
Security	TPM 2.0	**Operating System**	Windows 10 IoT Enterprise (64 bit) (Optional) Windows 11 IoT Enterprise (64 bit) (Optional) Windows 11 Pro 64 bit (Optional) Linux Ubuntu 24.04(Do not support Wake on Touch) (Optional)

Mechanical

Dimension	250 x 205 x 55 mm	**Weight**	3.0 kg
Mounting	Desk mount	**Enclosure**	Aluminum Housing
Cooling System	Fanless Design		

Environment

Operating Humidity	10% to 90% RH, Non-Condensing	**Operating Temperature**	-10°C to 45°C
Storage Temperature	-20°C to 60°C	**Shock**	Operating, IEC 60068-2-27
Vibration	Operating, IEC 60068-2-64	**IP rating**	IP65

Certification

WINMATE
No. 18, Zhongxing S. St., Sanchong Dist., New Taipei City 241017 , Taiwan (R.O.C.)
Tel: +886-2-8511-0288
Website: www.winmate.com

Revised:V.260303.260310

Certification	CE, FCC

IO Ports

Power Input	1 x M12 waterproof connector for 9~36V DC	**USB Port**	1 x M12 waterproof connector for 2 x USB2.0 1 x Waterproof USB Type-A Connector with cover
Serial Port	1 x M12 waterproof connector for RS232/RS422/RS485 (Default RS232)	**Video**	1x Waterproof connector for HDMI output
Expansion Port	1 x M.2 2230 E-Key Slot (for Wi-Fi Module)	**LAN**	1 x M12 type connector for Giga LAN
Indicator	1 x LED Indicator for power 1 x LED Indicator for storage 1 x LED Indicator for LAN		

Control

Button	1 x Power Button with LED Indicator

Accessory

Accessory	External open wire Power cable with waterproof connector External USB cable with waterproof connector External HDMI cable with waterproof connector External COM cable with waterproof connector External LAN cable with waterproof connector Waterproof caps RJ45 female-female converter	**Optional Accessory**	100~240V AC to DC Adapter with waterproof connector (Optional) Power Cord (Optional)

DIMENSIONS UNIT:MM



NOTE

1.This is a simplified drawing and some components are not marked in detail.
2.Please contact our sales representative if you need further product information.
3.All specifications are subject to change without prior notice.
4.The product shown in this datasheet is a standard model.For diagrams that contain customized or optional I/ O, please contact the Winmate Sales Team for more information.