

R10IAN3S-CHA1WT

10.4" Intel® Twin Lake N150 Chassis Wide Temperature Panel PC



CE

FC

KEY FEATURES

- 10.4" XGA TFT LCD
- Intel® Twin Lake N150 Processor
- 1 x SO-DIMM DDR5-4800, max. 16GB
- 2 x 2.5 Gigabit Ethernet
- Supports 1 x HDMI, 1 x USB 3.2 Type-C with DP-Alt, 2 x USB 3.2 Gen 2 Type-A, 4 x USB 2.0, 4 x COM
- Wide Temperature Chassis Panel PC
- Supports VESA Mount

INTRODUCTION

Winmate R10IAN3S-CHA1WT is a 10.4-inch Intel® Twin Lake N150 Chassis Wide Temperature Panel PC engineered for machine control, factory automation, and operator HMI. It combines 10.4-inch display, IP65, and 10.4" XGA TFT LCD to support reliable operation in harsh industrial environments. With Intel® Twin Lake N150 Processor, the R10IAN3S-CHA1WT helps OEMs, system integrators, and project teams deploy durable, configurable solutions for demanding field, factory, and mission-critical applications.

SPECIFICATIONS

Display

Resolution	800x600	Size	10.4 inches
Contrast Ratio	700:1	Panel Brightness	400.0 nits
View Angles	80,80,70,60	Active Area	211.2x158.4 mm
Touch / Glass	Resistive Touch Screen (Optional) Protection Glass Without Touch Function (Optional)		

System Specification

Processor	Intel® Processor N150 6M Cache, up to 3.60 GHz	Memory	8GB (Default) 16GB (Optional)
Storage	128GB SSD (Default) 256GB SSD (Optional) 512GB SSD (Optional) 1TB (Optional) 2TB (Optional) 1 x SATA III for 2.5" SSD/HDD up to 2TB (Only available when NVME SSD is not present) (Optional)	Ethernet controller	2 x Intel® 2.5 Gigabit Ethernet Controller
Security	TPM 2.0	Operating System	Windows 11 IoT Enterprise (64 bit) (Optional) Windows 11 Pro 64 bit (Optional) Linux Ubuntu 24.04 (Do not support Wake on Touch) (Optional)

Mechanical

Dimension	270 x 225 x 60 mm	Weight	2.6 kg
Mounting	VESA mount	Enclosure	Metal Housing
Cooling System	Fanless Design		

Environment

Operating Humidity	30% to 90% RH, Non-Condensing	Operating Temperature	-20°C to 60°C
Storage Temperature	-25°C to 65°C		

Certification

Certification	CE, FCC
---------------	---------

IO Ports

Power Input	1 x 12V DC, 2.5φ DC jack	USB Port	2 x USB3.2 Gen1x1 (Type-A) 1 x USB 3.2 Gen 2x1 Type C connector,support DP Alt. mode
Serial Port	1 x RS232/422/485 (Default RS232) 1 x RS232	Video	1 x HDMI 2.0b (Optional)
Audio	2 x Speaker	Expansion Port	1 x M.2 2230 E-Key Slot (for Wi-Fi module)
LAN	2 x 2.5 Giga LAN RJ45 Connector	Indicator	1 x LED Indicator for power 1 x LED Indicator for storage
Brightness Knob	1 x Brightness Adjustment Knob		

Control

Button	1 x Power Button 1 x Reset Button
--------	--------------------------------------


Accessory

Accessory	100~240V AC to DC Adapter Power Cord VESA screws
-----------	--

Power

Power Rating	12V DC	Adapter	12V 50W
--------------	--------	---------	---------

DIMENSIONS UNIT:MM



NOTE

1. This is a simplified drawing; some components are not marked in detail.
 2. Please contact our sales representative if you need further product information.
 3. All specifications are subject to change without prior notice.
 4. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/ O, please contact the Winmate Sales Team for more information.
- * Some images or content on this page are created or enhanced using generative AI technology. All AI-generated content has been reviewed before publication.