

W10IAN3S-GSH2

10.1" G-WIN GS-Series Full IP65 PCAP Panel PC with Intel® Processor N150



KEY FEATURES

- 10.1" 1280 x 800 Resolution with Projected Capacitive Multi-Touch (P-CAP)
- Low power consumption with Intel® Processor N150
- Fanless cooling system design
- Edge-to-edge design
- Full IP65 design with Special M12 Waterproof connectors
- 1 x GbE LAN, 1 x RS232, 1 x USB 2.0

INTRODUCTION

Winmate W10IAN3S-GSH2 is a 10.1-inch G-WIN GS-Series Full IP65 PCAP Panel PC with Intel® Processor N150 engineered for machine control, factory automation, and operator HMI. It combines Intel® Processor N150, 10.1-inch display with 1280x800 resolution, and IP65 to support reliable operation in harsh industrial environments. With 10.1" 1280 x 800 Resolution with Projected Capacitive Multi-Touch (P-CAP), the W10IAN3S-GSH2 helps OEMs, system integrators, and project teams deploy durable, configurable solutions for demanding field, factory, and mission-critical applications.

SPECIFICATIONS

Display

Resolution	1280x800	Size	10.1 inches
Contrast Ratio	800:1	Panel Brightness	350.0 nits
View Angles	85,85,85,85	Active Area	216.96x135.6 mm
Touch / Glass	Projected Capacitive Multi Touch Screen (Default) Protection Glass (Optional)		

System Specification

Processor	Intel® Processor N150 6M Cache, up to 3.6 GHz	Memory	8GB (Default) 16GB (Optional)
Storage	128GB SSD (Default) 256GB SSD (Optional) 512GB SSD (Optional) 1TB (Optional) 2TB (Optional)	Ethernet controller	1 x Intel® Gigabit Ethernet Controller
Security	TPM 2.0	Operating System	Windows 11 IoT Enterprise (64 bit) (Optional) Windows 11 Pro 64 bit (Optional) Linux Ubuntu 24.04 (Optional)
WLAN	(Optional)	BT	(Optional)

Environment

Operating Humidity	10% to 95% RH	Operating Temperature	-15~55°C
Storage Temperature	-30°C to 60°C	Shock	40g for 11ms
Vibration	1.48/1.90/2.24 g rms for XYZ/ 5-500Hz	IP rating	IP65, Dustproof and Waterproof

Certification

Certification	CE, FCC
---------------	---------

Compliant with MIL-STD-810F/G for vibration / shock

IO Ports

USB Port	1 x USB 2.0 (M12 type)	Serial Port	1 x RS232/422/485 (Default RS232)(M12 type)
LAN	1 x LAN-10/100/1000 (M12 type)	Indicator	1 x LED Indicator for power 1 x LED Indicator for storage

Mechanical

Dimension	263.28 x 172 x 40.2 mm	Mounting	VESA mount (Default) Front IP65 Panel mount (Optional)
Enclosure	Aluminum	Cooling System	Fanless Design

Power

Power Rating	9-36V DC (M12 type)
--------------	---------------------


Accessory

Accessory	Quick Start Guide (Hardcopy) M12 Power Cable M12 Serial Interface Cable M12 USB/ LAN Cable I/O Protective Cap x 3
-----------	---

Control

Button	1 x Power Button 1 x Reset Button
--------	--------------------------------------

DIMENSIONS UNIT:MM



NOTE

1. This is a simplified drawing and some components are not marked in detail.
 2. Please contact our sales representative if you need further product information.
 3. All specifications are subject to change without prior notice.
 4. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.
- * Some images or content on this page are created or enhanced using generative AI technology. All AI-generated content has been reviewed before publication.