

W22L100-PMB1OD

21.5" Resistive Touch Panel Mount Display



CE

FCC

KEY FEATURES

- Sunlight readable with high brightness solution
- Support panel mount
- Operating temperature: -10~60°C
- Optional operating temperature : -25~60°C with heater solution
- Support resistive touch
- Optional solar radiation protection with UV film for directed sunlight environment

INTRODUCTION

Winmate Panel Mount Display Series combines durability and versatility for industrial and commercial applications. Available in sizes from 5.7" to 32", these wide displays feature high brightness up to 1300 nits for excellent visibility, even in bright environments. With VGA and HDMI interfaces, panel mount, and VESA mount options, they ensure seamless integration with various systems. Customizable to meet specific requirements, this display series is ideal for factory automation, kiosks, and control rooms, offering reliable performance and adaptability.

SPECIFICATIONS

Display			
Resolution	1920x1080	Size	21.5 inches
Contrast Ratio	1000:1	Panel Brightness	1000.0 nits
Display Color	16.7M Colors	View Angles	90,90,90,90
Active Area	476.64x268.11 mm	Touch / Glass	Resistive Touch Screen Protection Glass w/o Touch Function (Optional)
Environment			
Operating Humidity	10% to 90% RH, Non-Condensing	Operating Temperature	-10°C to 60°C
Storage Temperature	-20°C to 70°C		
Certification			
Certification	CE, FCC		
IO Ports			
USB Port	1 x USB for Touch Screen	Video	1 x VGA 1 x HDMI (Optional) 1 x DVI (Optional)
Audio	Audio line in (3.5mm) (Optional) 2 x Speaker (Optional)		
Mechanical			
Dimension	534 x 349 x 66 mm	Mounting	VESA Mount/ Panel Mount
Enclosure	Metal Housing with Aluminum Bezel	Cooling System	Fanless Design
Cut out	510 x 322mm		

